

## **TOOL FEATURES**

- 1. Rotatable exhaust on enduring engine.
- 2. Sequential trigger lock ensures workplace safety.
- 3. Nail tip guide, places fastener point directly into connector holes for a fast and precise application.
- 4. Metal belt hook provides workplace convenience.
- 5. Cushioned grip ergonomic frame provides comfort during operation.
- 6. Aluminum magazine, in-line design offers balance for maneuverability.
- · Low nail lockout prevents dry fires.
- · Anti nail back up pawl boosts operation stability.
- · Compact design fits between 12" O.C. joists.
- · Two trigger options available : MCN40B-ST (sequential) / MCN40B-CT (contact)





FASTENER SPECS	
Туре	34° Papper Collated Nails
Loading Capacity	33
Α	38~40mm (1-1/2")
В	7.01~7.36mm (0.276"~0.290")
С	3.3mm~3.8mm (0.131"~0.148")



TOOL SPECS	
Weight	2.0 kgs (4.4 lbs)
Height	275mm (10.8")
Width	92mm (3.6")
Length	298mm (11.7")
Operating Pressure	5~8 bar (70~120 psi)
Driving Power	59+ In-lbs @100 psi
Applications	Strapping, Joist Hangers, Hurricane Ties, Rafter Ties, Post Bases, Caps Anchors

