

TOOL FEATURES

1. Rear adjustable directional exhaust.
2. Durable driver / bumper provides reliability.
3. One-hand manual rear latch.
4. Robust metal magazine.
5. Fast, sensitive trigger.
6. 2" (50mm) extra long nose version available : LN series.
 - Optional safety double trigger
 - Rapid Cycling engine.




US series
Single fire, short nose

LN series
Single fire, long nose

FASTENER SPECS

Loading Capacity	100~180
A	5~16mm (3/16"~5/8")
Except US1013F(LN)&US1013J(LN):5~13mm(3/16"~1/2")	
US8025: 6~25mm(1/4"~1")	



TOOL SPECS

Weight	0.9 kgs (2.0 lbs) US8025 : 1.2 kgs (2.6 lbs)
Height	Short Nose : 140mm (5.5") Long Nose : 197mm (7.8") US8025 : 180mm (7.1")
Width	38mm (1.5") US8025 : 55mm (2.2")
Length	216mm (8.5") US8025 : 215mm (8.5")
Operating Pressure	5~6.9 bar (70~120 psi)
Driving Power	51 In-lbs @100 psi
Applications	Furniture Upholstery, Automotive Vinyl, Trim

Model Number	B	C	Capacity	Wire Gauge
USSJK16	4.1mm (5/32")	0.60 x 0.74mm (0.024" x 0.030")	150	22 GA. Atro SJK
US9716	4.5mm (3/16")	0.65 x 0.95mm (0.026" x 0.037")	100	21 GA. BeA 97 / Senco W
US5416 / US5416LN	4.7mm (3/16")	0.50 x 1.25 mm (0.020 x 0.049")	100	20 GA. Duo-Fast 54 / Senco E
USSNCW16 / USSNCW16LN	4.8mm (3/16")	0.69 x 0.90 mm (0.027" x 0.035")	100	21 GA. Senco W
USSNCA16 / USSNCA16LN	4.85mm (3/16")	0.60 x 0.74mm (0.024" x 0.030")	150	22 GA. Senco A / Prebena U
US416J / US416JLN	5.25mm (7/32")	0.56 x 1.16mm (0.022" x 0.045")	100	20 GA. Duo-Fast 63
US9916	5.4mm (7/32")	0.59 x 0.98mm (0.021" x 0.040")	100	21 GA. Atro 99 / Prebena ED
US7116 / US7116LN	9.1mm (3/8")	0.60 x 0.75mm (0.024" x 0.030")	180	22 GA. 71 Series / Senco C
USSNCG16 / USSNCG16LN	9.5mm (3/8")	0.60 x 1.30mm (0.024" x 0.051")	100	20 GA. Senco G
USA1116 / USA1116LN	10.8mm (7/16")	0.50 x 1.22mm (0.020" x 0.048")	100	20 GA. Fasco A11 / Arrow T50
US1013F / US1013FLN	11.2mm (7/16")	0.50 x 0.70mm (0.020" x 0.028")	150	23 GA. MAX 10F (1000F)
US1013J / US1013JLN	11.2mm (7/16")	0.60 x 1.20mm (0.024" x 0.047")	150	20 GA. MAX 10J (1000J)
US8416 / US8416LN	12.3mm (1/2")	0.55 x 1.00mm (0.022" x 0.039")	100	21 GA. Bostitch SBNK / Fasco 84
US6416 / US6416LN	12.45mm (1/2")	0.51 x 0.73mm (0.024" x 0.030")	150	22 GA. Atro 6 / BeA 64
US50(95)16 / US50(95)16LN	12.55mm (1/2")	0.50 x 1.25mm (0.020" x 0.049")	100	20 GA. Duo-Fast 50 / BeA 95
US8016 / US8016LN	12.8mm (1/2")	0.63 x 0.90mm (0.025" x 0.036")	150	21 GA. 80 Series / Senco AT
USSNCF16 / USSNCF16LN	12.8mm (1/2")	0.50 x 1.25mm (0.020" x 0.049")	100	20 GA. Senco F / Prebena P
US8025	12.8mm (1/2")	0.63 x 0.90mm (0.025" x 0.036")	150	21 GA. 80 Series / Senco AT

